## MDF Cable Bus Request for Quote Form

	0
Requestors Name:	Project Name:
Requestors Company:	Location:
Address:	Owner:
Phone: Fax:	Engineer:
Email:	Bid Date: Ship Date:
Voltage:	Total Overall Cable Bus Footage:
Current Rating:	Horizontal Footage (All runs)
System Configuration:	Vertical Footage (All Runs)
, 3 Phase / 3 Wire	Total Footage (All runs)
3 Phase / 4 Wire Full Neutral	Number of Bus Runs
3 Phase / 4 Wire Half Neutral	
3 Phase / 4 Wire% Neutral	Total Overall Quantities:
Single Phase AC	Horizontal 90 Deg Elbow
Two Pole DC	Horizontal 45 Deg Elbow
Other	Vertical 90 Deg Elbow
	Vertical 45 Deg Elbow
Ambient Temperature Other than (40° C)	Wall Seal (Environmental Seal)
Cable Operating Temperature Other than (90° C)	Fire Rated Wall Seal
came operating reinperatore officer fitting (50 C)	Tap Box (with Bus Bars & Insulators)
Conductor Material:	Transition Box (Top Hat/Pull Box)
	Splice Box
Copper	Spince BoxIndoor Equipment Seal Plate
Aluminum	Horizontal Outdoor Equipment Seal Plate
(00 Vals Calda la collation	Vertical Outdoor Equipment Seal Plate (Water tight)
600 Volt Cable Insulation:	vernicui ooraoor Eqoipineni Searriale (water nyin)
XLP (XHHW-2)	
Other	
Enclosure Ground: External Ground:	List Other Special Requirements:
5kV & 15kV Cable Insulation:	
EPR	
Other	
5kV & 15kV Cable Jacket Material:	
PVC	
Other	
Short circuit Rating:	
65 kA Other:	
100 kA	

ph: 888-808-1655

Fax: 859-586-6515

email:sales@mdfbus.com